

lurray seating | product specification

Pedestal Base Chairs

Models: 6460PB, 6461PB, 6462PB

Dimensions

Overall Depth		26.5 in / 673 mm
Overall Width		25 in / 635 mm
Overall Height	6460PB	44.5-46.5 in / 1130-1181 mm
	6461PB	41-43 in / 1041-1092 mm
	6462PB	38-40 in / 965-1016 mm
Seat Depth		19 in / 483 mm
Seat Width		20 in / 508 mm
Seat Height		17-19 in / 432-483 mm
Back Height	6460PB	27.5 in / 699 mm
	6461PB	24 in / 610 mm
	6462PB	21 in / 533 mm
Armrest Clearance		19.5 in / 495 mm
Arm Height - From Seat		8 in / 203 mm
Product Weight	6460PB	39 lb / 17.7 kg
	6461PB	37 lb / 16.8 kg
	6462PB	35 lb / 15.9 kg
Shipment Weight	6460PB	47 lb / 21.4 kg
	6461PB	45 lb / 20.5 kg
	6462PB	41 lb / 18.6 kg
Shipping Cube	6460PB	14.75 ft³ / 0.42 m³
	6461PB,	13.75 ft³ / 0.39 m³
	6462PB	

Contact sales representative for more information.

Features

- Three back heights are available, with horizontal stitch details
- Pedestal base secures chair to the floor while allowing chairs to swivel
- Mechanism provides 2 in (51 mm) pneumatic seat
- Soft decent pneumatic cylinder with automatic return to maximum height and return to center

Options

- Cylinders that do not automatically return to center or do not swivel, are available. These optional cylinders automatically return to maximum height
- Stitch detail is discrete, matching thread, as standard. Exaggerated top stitch detailing is available 14 colors
- Polished aluminum arms are available with Self-Skinned Urethane (SSU) armcaps or wood armcaps
- Standard seat foam may be replaced with memory foam

Construction (Arms)

- Black, fixed loop arms
- Fiberglass reinforced nylon
- SSU armcaps with waterfall front edge

Construction (Seat)

- Plywood seat pan, 0.5 in (13 mm) thick, 8-ply

Construction (Back)

- Plywood back, 0.5 in (13 mm) thick, 7-ply



6460PB



6461PB



6462PB



luray seating | product specification

Construction (Base)

- Metal base plate with black metal cover and black cylinder cover
- See installation guide (available on our installation guide web page)
- Base plate mounts to floor. Mounting hardware not included

Construction (Mechanism)

- Constructed of cast aluminum and stamped steel
- Connected to gas-assisted pneumatic cylinder

Upholstery

- Chair can be upholstered in fabric, vinyl or leather
- Front edge of seat is a seamless waterfall
- Optional exaggerated stitch detail on chair back

Foam (Seat)

- 2.5 in (64 mm) thick foam
- Density: 1.8 lb, ILD: 50

Foam (Back)

- Dual layer back foam:
 - 1 in (25 mm) thick layer, Density: 1.9 lb, ILD: 27
 - 0.5 in (13 mm) thick top layer, Density: 1.8 lb, ILD: 50

Weight Capacity

Designed for an active weight capacity of 300 lb.

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foam and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental

View [Environmental Data Sheets](#) online. All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.

